

OT-100 Ordering Terminal

- Small and discreet, with a stunning 4.3" touchscreen LCD
- Good visibility outdoors
- Wireless
- Vibration alert
- Auto-rotation of display
- Spill resistant and dust resistant (IP54)
- Ruggedized to withstand up to 1.2 meter drops
- Future proof with add-on modules (RFID, MSR, Barcode Scanner)



OT-100 Ordering Terminal

Partner Tech is pleased to present OT-100, the revolutionary ordering terminal handheld.

The functionality and stylish appearance of the OT-100 is ideally suited to the hospitality environment thanks to its compact size, lightweight design, and durability. Orders can be transmitted directly from the OT-100 to the bar or kitchen via WiFi, allowing your employees to spend more time with guests and less time walking back and forth.

With its touch-enabled 4.3" widescreen LCD, integrated WiFi, 1.2 meter drop test and IP54 rating, OT-100 is a cost effective handheld terminal which will enhance any hospitality solution.

Benefits of using OT-100

- Reduces time spent on order taking and keying orders into POS system ~ information is directly transmitted via wireless to POS terminal and kitchen.
- Improves staff efficiency by eliminating need for waiters to go to kitchen to deliver orders
- Order processing time is immediate since kitchen receives order right away, allowing for quicker service, and higher table turnover
- Improved accuracy of order taking
- With its stylish and modern design, coupled with the latest technology, OT-100 will impress guests and enhance their customer experience



Add-on RFID module



Add-on MSR module



Add-on Barcode Scanner module



Support Sunlight-readable panel



Packed with comprehensive accessories



OT-100 Ordering Terminal	
CPU	Freescale i.MX31L CPU @ 532MHz with system bus at 133MHz
Operating System	Microsoft Windows™ CE 5.0
Display	4.3" TFT LCD with Touch Screen, widescreen 272*480
Memory	128MB NAND Flash, 128MB Mobile DDR RAM
Communication	WiFi 802.11b/g
Extension slot	SD card (supports SDHC up to 16G)
Interface	Mini-USB 2.0
Other	4-way direction sensor (for auto-rotation) Vibrator motor (for alerts) Speaker Earphone jack (3.5") Microphone jack (2.5")
Features	Wireless roaming SSID Lock Battery cover safety protection Remote Desktop Lock screen
Ruggedness	IP54 1.2 meter drop tested
Environmental	Operating temperature: 0° C to 40° C Storage temperature: -20° C to 60° C Operation and storage humidity: 15% to 80%
Battery	Rechargeable Li-ion battery 2300mAh (removable)
Power adaptor	5V 2A
Dimensions (WxLxH)	82 * 133 * 19 mm
Weight	Approximately 220g with battery
Optional modules	RFID module (Mifare 13.56 MHz) MSR module (Track 1, 2, 3) Barcode scanner module (1D)
Accessories	AC adaptor, Cradle, Battery, Stylus cord, Hand strap, Leather pouch, Leather pouch cord, Shoulder strap, High quality stylus
Certifications	RF: FCC / CE / NCC (for WiFi 802.11b/g, RFID) EMC: FCC / CE / BSMI / VCCI Safety: LVD / BSMI / CB (IEC60950-1:2005 / EN60950-1:2001, 1st ed.)

*specification subject to change without prior notice



Partner Tech Corporation

Taiwan	TEL:+886-2-29188500	FAX:+886-2-29153405	E-mail:sales@partnertech.com.tw
USA	TEL:+1-949-598-1888	FAX:+1-949-598-0088	E-mail:sales@partnertechcorp.com
Europe	TEL:+49 (0)40 450 635-0	FAX:+49 (0)40 450 635-130	E-mail:info@partnertech.eu
UK	TEL:+44 (0)1928 579 707	FAX:+44 (0)1928 571 308	E-mail:sales@partnertech-uk.com
China	TEL:+86-21-67696667	FAX:+86-21-67696699	E-mail:sales@partnertech.com.cn
Korea	TEL:+82-2-2090-7559	FAX:+82-2-2090-7558	E-mail:adams_c@partnertech.com.cn

